

UL / CSA Maximum HP Rating Selection ❶

Sprecher + Schuh Contactor Series	Maximum Horsepower					
	Single Phase		Three Phase			
	115 Volt	230 Volt	200 Volt	230 Volt	460 Volt	575 Volt
CA7-9	1/2	1 1/2	2	2	5	7-1/2
CA7-12	1/2	2	3	3	7-1/2	10
CA7-16	1	3	5	5	10	15
CA7-23	2	3	5	7-1/2	15	15
CA7-30	2	5	7-1/2	10	20	25
CA7-37	3	5	10	10	25	30
CA7-43	3	7-1/2	10	15	30	30
CA7-60	5	10	15	20	40	50
CA7-72	5	15	20	25	50	60
CA7-85	7-1/2	15	25	30	60	60
CA7-97	10	20	30	30	75	75
CA6-115(-EI)	10	25	40	40	75	100
CA6-140(-EI)	15	30	40	50	100	125
CA6-180(-EI)	~	40	50	60	150	150
CA6-210-EI	~	50	60	75	150	200
CA6-250-EI	~	~	75	100	200	250
CA6-300-EI	~	~	100	125	250	300
CA6-420-EI	~	~	150	175	350	400
CA5-700	~	~	200	250	500	500
CA6-630-EI	~	~	200	250	500	600
CA5-860	~	~	250	300	600	600
CA6-860-EI	~	~	250	300	600	700
CA5-1200	~	~	450	450	900	900

NEMA Size Labeled Selection ❶

NEMA Size	Sprecher + Schuh Contactor Series	Maximum Horsepower					
		Single Phase		Three Phase			
		115V	230V	200V	230V	460V	575V
00	CAN7-12	1/3	1	1-1/2	1-1/2	2	2
0	CAN7-16	1	2	3	3	5	5
1	CAN7-37	2	3	7-1/2	7-1/2	10	10
2	CAN7-43	3	7-1/2	10	15	25	25
3	CAN7-85	7-1/2	15	25	30	50	50
4	CAN6-180	~	~	40	50	100	100
	CAN6-180-EI	~	~	40	50	100	100
5	CAN6-300-EI	~	~	75	100	200	200

❶ "EI" designation indicates coil has electronic interface capability with a PLC.